



- LEGEND**
- P.R.M. FOUND (CONCRETE MONUMENT)
 - P.R.M. SET (CONCRETE MONUMENT)
 - ▣ P.R.M. (CONCRETE MONUMENT REPLACING IRON PIPE FOUND)
 - P.R.M. (IRON PIPE FOUND)
 - × P.R.M. (CHISEL CUT FOUND)
 - ⊙ P.C.P. (PERMANENT CONTROL POINT)
 - BREAK POINT
- NOTE: P.R.M. IS ABBREVIATION FOR PERMANENT REFERENCE MONUMENT

NO	△	CURVE DATA			CH. BEAR.	CHORD
		RAD	ARC	TAN		
1	56° 01' 56"	150.00	146.69	79.81	N63°36' 25" E	140.92
2	10° 44' 49"	600.00	112.54	56.44	N86°14' 59" E	112.38
3	10° 58' 54"	600.00	115.00	57.68	N75°23' 07" E	114.82
4	60° 40' 11"	140.00	148.24	81.92	N58°02' 32" W	141.42
5	06° 07' 24"	375.00	40.08	20.06	S88°33' 41" W	40.06
6	56° 00' 00"	100.00	97.74	53.17	S63°37' 23" W	93.89
7	60° 40' 11"	150.00	158.83	87.78	N58°02' 32" W	151.52
8	90° 00' 00"	50.00	78.54	50.00	N46°37' 23" E	70.71
9	62° 00' 00"	50.00	54.11	30.04	S57°22' 37" E	51.50
10	22° 46' 35"	425.00	168.95	85.60	S76°59' 20" E	167.84
11	21° 43' 43"	425.00	161.88	81.57	N80°45' 32" E	160.21
12	88° 50' 20"	25.00	38.76	24.50		35.00
13	83° 33' 34"	25.00	36.46	22.34	S20°30' 47" W	33.31
14	90° 00' 00"	25.00	39.27	25.00		35.36
15	60° 40' 11"	165.00	174.72	96.55	N58°02' 32" W	166.67
16	76° 39' 27"	15.00	20.07	11.86	N53°17' 40" E	18.61
17	11° 11' 29"	425.00	83.01	41.64	N60°00' 18" W	82.88
18	15° 21' 28"	375.00	101.61	51.12	S62°10' 17" E	101.30
19	56° 01' 56"	125.00	122.24	66.51	S63°36' 25" W	117.43
20	05° 42' 07"	625.00	62.20	31.12	N88°45' 20" E	62.17
21	09° 06' 31"	625.00	99.36	49.78	S81°22' 01" W	99.25
22	06° 55' 05"	625.00	75.47	37.78	S73°21' 13" W	75.42
23	91° 09' 40"	25.00	39.78	25.51	N24°18' 50" E	35.71
24	15° 36' 19"	375.00	102.14	51.39	S77°41' 50" W	101.82
25	18° 26' 36"	375.00	120.71	60.88	S79°09' 19" E	120.19
26	60° 40' 11"	115.00	121.77	67.29	N58°02' 32" W	116.16
27	16° 39' 27"	50.00	145.44	427.49	S81°42' 21" E	99.32
28	90° 00' 00"	50.00	78.54	50.00	S46°37' 23" W	70.71

SMALLY, WELLFORD & NALVEN
 CONSULTING ENGINEERS
 SARASOTA, FLORIDA